

POWERSTREAM 4SH | 4 Steel Wire Spiral EN 856 4 SH

TUBE : MINERAL, VEGETABLE, AND GLYCOL BASED HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.



Dash Size	ID		ROD	OD	WP		BP		BR/r	W
	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
-10	5/8"	16	25.3	28.7	420	6090	1680	24360	240	1225
-12	3/4"	19	28.2	32	420	6090	1680	24360	280	1500
-16	1"	25.4	35.1	38.4	380	5510	1520	22040	340	2065
-20	1 1/4"	31.8	41.9	45.2	350	5075	1400	20300	460	2425
-24	1 1/2"	38.1	48.8	53	290	4205	1160	16820	560	3235
-32	2"	50.8	63.2	67.6	250	3625	1000	14500	700	4460



-40°C / +100°C (+125°C DISCONTINUOUS)
 -40°F / +212°F (+257°F DISCONTINUOUS)

MiCS POWERSTREAM 4SH TS 10548/EN 856 4SH ()** (DN ** mm) Max W P *** Bar / **** PSI MSHA IC-215/0

Tagline in hose

MiCS || QUICK SOLUTIONS || MICSHOSES.COM

EN 856 4SH 1" - DN25- WP 380 BAR / 5510 PSI