



POWERSTREAM 4SP

4 Steel Wire Spiral

EN 856 4SP / SAE 100 R9R

TUBE : MINERAL, VEGETABLE, AND GLYCOL BASED HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.



Dash Size	ID		ROD	OD	WP		BP		BR/r	W
	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
-04	1/4"	6.4	14.6	17.6	450	6525	1800	26100	150	585
-06	3/8"	9.5	17.5	21.2	445	6453	1780	25810	180	750
-08	1/2"	12.7	20.3	24.4	415	6018	1660	24070	230	890
-10	5/8"	16	23.8	28	350	5075	1400	20300	250	1070
-12	3/4"	19	28.2	32	350	5075	1400	20300	300	1500
-16	1"	25.4	35.1	39.1	280	4060	1120	16240	340	1915



-40°C / +100°C (+125°C DISCONTINUOUS)
 -40°F / +212°F (+257°F DISCONTINUOUS)

MiCS POWERSTREAM 4SP TS 10548/EN 856 4SP ()** (DN ** mm) Max. W.P. *** Bar / **** PSI MSHA IC-215/0

Tagline in hose

MiCS || QUICK SOLUTIONS || MICSHOSES.COM

EN 856 4SP/SAE 100 R9R 1" - DN25- WP 280 BAR / 4060 PSI