



R12

4 Steel Wire Spiral Exceed EN 856 R12

TUBE : MINERAL, VEGETABLE, AND GLYCOL BASED HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.



Dash Size	ID		ROD	OD	WP		BP		BR/r	W
	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
-06	3/8"	9.5	17.1	20	280	4060	1450	21025	100	615
-08	1/2"	12.7	20.5	23.5	280	4060	1400	20300	125	775
-10	5/8"	16	24.6	27.6	280	4060	1350	19575	140	1060
-12	3/4"	19	27.5	30.5	280	4060	1350	19575	150	1200
-16	1"	25.4	35.1	38.1	280	4060	1300	18850	225	1820
-20	1 1/4"	31.8	43.6	46.6	210	3045	1100	15950	250	2550
-24	1 1/2"	38.1	50.1	53.2	175	2538	1100	15950	500	2980
-32	2"	50.8	63.7	66.8	175	2538	900	13050	650	4170



-40°C / +120°C (+125°C DISCONTINUOUS)
 -40°F / +248°F (+257°F DISCONTINUOUS)

MiCS R12 TS 10548/EN 856 R12 (") (DN ** mm) Max. W.P. *** Bar / **** PSI MSHA IC-215/0**

Tagline in hose

MiCS || QUICK SOLUTIONS || MICSHOSES.COM

SAE 100 R12 /EN 856 R12 1" - DN25- WP 280 BAR / 4060 PSI