



R13

4 - 6 Steel Wire Spiral Exceed EN 856 R13

TUBE : MINERAL, VEGETABLE, AND GLYCOL BASED HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 OR 6 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.



Dash Size	ID		ROD		OD		WP		BP		BR/r		W	
	inch	mm	mm	mm	mm	mm	bar	psi	bar	psi	mm	mm	g/m	g/m
-12	3/4"	19	29	32	350	5075	1800	26100	240	1635				
-16	1"	25.4	35.1	38.4	350	5075	1750	25375	300	2080				
-20	1 1/4"	31.8	46.3	49.3	350	5075	1700	24650	420	3885				
-24	1 1/2"	38.1	53.7	57.3	350	5075	1650	23925	500	4870				
-32	2"	50.8	68	71.6	350	5075	1500	21750	630	6460				



-40°C / +120°C
 -40°F / +248°F

(+125°C DISCONTINUOUS)
 (+257°F DISCONTINUOUS)

MiCS R13 TS 10548/EN 856 R13 (") (DN ** mm) Max. W.P. *** Bar / **** PSI MSHA IC-215/0**

Tagline in hose