



R15

4 - 6 Steel Wire Spiral Exceed EN 856 R15

TUBE : MINERAL, VEGETABLE, AND GLYCOL BASED HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 OR 6 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.



Dash Size	ID		ROD	OD	WP		BP		BR/r	W	L
	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	m
-06	3/8"	9,5	17,5	21,2	420	6090	2050	29725	110	760	> 3
-08	1/2"	12,7	20,3	24,4	420	6090	1800	26100	120	900	> 3
-10	5/8"	16	25,3	28,7	420	6090	1800	26100	200	1250	> 3
-12	3/4"	19	28,2	32	420	6090	1760	25520	265	1515	Max. 61
-16	1"	25,4	35,1	38,4	420	6090	1760	25520	270	2085	Max. 61
-20	1 1/4"	31,8	46,3	49,3	420	6090	1750	25375	270	3885	Max. 61
-24	1 1/2"	38,1	53,7	57,3	420	6090	1750	25375	315	4870	Max. 61
-32	2"	50,8	68,4	72	420	6090	1680	24360	600	6610	Max. 61



-40°C / +120°C (+125°C DISCONTINUOUS)
 -40°F / +248°F (+257°F DISCONTINUOUS)

MiCS R13 SAE 100 R15 ()(DN ** mm) Max. W.P. *** Bar / **** PSI MSHA IC-215/0**

Tagline in hose

MiCS || QUICK SOLUTIONS || MICSHOSES.COM

SAE 100 R15 1" - DN25- WP 420 BAR / 6090 PSI